

WA-200 Series

AUTOMATIC SPRAY GUN

- Fluid needle packing in PTFE
- Weight: only 500 g.
- Fluid nozzle + Fluid needle set in stainless steel
- Fluid nozzle + Fluid needle set in tungsten carbide available
- Gun body insert in stainless steel

Certificate of Compliance issued by THATCHAM certifies that "Transfer Efficiency" achieved with the materials detailed in the test report were:

PRIMER : 93.2%
 SOLID COLOUR: 85.9%
 BASECOAT: 82.3%
 CLEAR LACQUER: 77.4%



MODEL	 Ø mm	 No.	 bar	 m ³ /min	 N ^l /min	 mm
-------	--	---	---	---	---	--

WA-200 WB							
WA-200 WB-081P	0.8	WB1	1.6	200	340	360	
WA-200 WB-101P	1.0			250			
WA-200 WB-121P	1.2			300			340
WA-200 WB-141P	1.4						
WA-200 WB-161P	1.6						

WA-200										
WA-200-062	0.6	LV2	2.0	255	270	280				
WA-200-084	0.8									
WA-200-104	1.0									
WA-200-124	1.2									
WA-200-154	1.5									
WA-200-082P	0.8	G2P	3.0	500	530	400				
WA-200-102P	1.0									
WA-200-122P	1.2									
WA-200-152P	1.5						K2	270	330	340
WA-200-202P	2.0						R2	400	360	320
WA-200-251P	2.5						W1	500		

WA-200 FLAT AND THIN®										
WA-200-066P FT	0.6	FT6	0.14	80	170	140				
WA-200-086P FT	0.8						0.16	100	185	150
WA-200-106P FT	1.0						0.18	120	200	160
WA-200-126P FT	1.2						0.20	140	220	180
								140	220	180



declaration of ATEX conformity for use in zone 1 and in zone 2

• Air nipple: G1/4" • Fluid nipple: G1/4"